

# Quantum® ELMRE

Contemporary Commercial LED Emergency Remote Lights

## Life Depends on It

The Lithonia Lighting® emergency line of products has expanded to include newly designed Quantum® indoor remotes. The ELMRE is designed to match the appearance of the Quantum units to use as part of an emergency lighting system, providing light for the path of egress. With fully adjustable or fixed optics, these compact and low-profile remotes provide high-quality light output when it is needed most.

The optical performance of the Quantum® series has raised the bar for path of egress coverage and spacing, allowing fewer products to do the same job, reducing the total product needed and lowering installation time and costs.

### Features and Benefits











































- UL damp location listed standard
- Wet location listed when used with the WPVS accessory
- Fixed and adjustable optics
- Universal DC Voltage (5VDC-30VDC) to accompany multiple battery voltages
- Compatible with self-diagnostics units
- Flexible conduit entry provision for easy wall or ceiling mount installation



Learn more about the ELMRE Emergency Remote Light at [www.Lithonia.com](http://www.Lithonia.com)

# Quantum® ELMRE Remote Light Heads

Refer to product specification sheets for further details.

Emergency Light	Battery Voltage & Capacity	Application		ELMRE Compatitible Remotes		Alternate Compatible Remotes (Not Compatible with SDRT Models)	
				ELMRE 5-30VDC; LP220=1.2W, SP640L=3.3W, SP1100L=5.3W (per lamp)	ELMRW	ELA Q & QWP= 9.6V, 1.5W (per lamp); LT24 = 6-18VDC, 2.5W(LP03VS) and 5.5W (LP05VS)	ELA LED Square 9.6V, 1W (per lamp)
 ELM2L LTP	9.6V 4.8-watts	Powering Lamps <2 watts	Indoor	 ELMRE LP220L   ELMRE T LP220L   ELMRE LP220L FXO	Not Applicable	 ELA Q	 ELA LED   ELA LED T   ERE SGL   ERE T
 ELM2LF LTP			Outdoor	 ELMRE T LP220L or ELMRE SGL LP220L With WPVS W SML   ELMRE LP220L FXO With WPVS W SML	    Coming Soon	 ELA QWP L0309	 ELA LED WP   ELA LED TWP   ERE SGL WP   ERE TWP
 ELM4L LTP	9.6V 11-watts	Powering Lamps >2 watts	Indoor	 ELMRE SP640L   ELMRE T SP640L   ELMRE SP1100L   ELMRE T SP1100L	Not Applicable	 ELA Q L0309   ELAT Q L0309  Compatible with SDRT Models  ELA SGL LT24   ELAT LT24	 ELA LED   ELA LED T   ERE SGL   ERE T
 ELM6L LTP	EHO 12.6V 32-watts		Outdoor	 WPVS SML Compatible with all ELMRE types	    Coming Soon	 ELA QWP L0309   ELAT QWP	 ELA LED WP   ELA LED TWP   ERE SGL WP   ERE TWP

Visit [www.Lithonia.com](http://www.Lithonia.com) for more information.