



The Holophane® and AEL® products you know and love are now in stock

Our traditionally made-to-order products now have inventory in our Dallas distribution center. Same quality, service, and 5-year product warranty that you expect from Holophane with a quicker lead time.

Class I Div II Low Bays- Hazardous Rated

	Product Description	Product Number	Lumens	Voltage	CI Code
	Petrolux LED hazardous low bay, medium glass lens with minimal uplight, universal mount, gray, super durable paint	PXLH 5000LM MD0 MVOLT 50K 70CRI UNM DGXD	5000	120-277V	*26228S
		PXLH 5000LM MD0 480 50K 70CRI UNM DGXD	5000	480V	*271H36
		PXLH 8000LM MD0 MVOLT 50K 70CRI UNM DGXD	8000	120-277V	*2593U5
		PXLH 5000LM MD0 480 50K 70CRI UNM DGXD	8000	480V	*26683A
	P3US stanchion/wall mounting arm accessory	P3US DGXD CR	N/A	N/A	*252GJ4
		P3US35 DGXD CR	N/A	N/A	*252CLS

Class I Div II Low Bays with Top Hat Adapter to Crouse Hinds- Hazardous Location

	Product Description	Product Number	Lumens	Voltage	CI Code
	Petrolux LED hazardous low bay, medium glass lens with minimal uplight, adapter ring for use with crouse hinds champ, 0° orientation, gray, super durable paint	PXLH 5000LM MD0 MVOLT 50K 70CRI ARCH00 DGXD	5000	120-277V	*26488V
		PXLH 5000LM MD0 480 50K 70CRI ARCH00 DGXD	5000	480V	*27924V
		PXLH 8000LM MD0 MVOLT 50K 70CRI ARCH00 DGXD	8000	120-277V	*2771KH
		PXLH 8000LM MD0 480 50K 70CRI ARCH00 DGXD	8000	480V	*27924U

Class I Div II Flood Lights- Hazardous Rated

	Product Description	Product Number	Lumens	Voltage	CI Code
	Predator medium LED hazardous C1D2 flood, 3 LED modules, 6x6 prismatic glass, yoke mount galvanized, 3G vibration rated, power cord 12 gage, 3 conductor with wiring box, gray, super durable paint	HPFM 3MOD 66PG MVOLT 50K YMG2 0423 1050MA DGXD	15000	120-277V	*27924Y
		HPFM 3MOD 66PG 480 50K YMG2 0423 1050MA DGXD	15000	480V	*27925A
		HPFM 6MOD 66PG MVOLT 50K YMG2 0423 1050MA DGXD	28000	120-277V	*2741V2
		HPFM 6MOD 66PG 480 50K YMG2 0423 1050MA DGXD	28000	480V	*27925F
	8657 GR tenon adapter	8657 GR	N/A	N/A	*116E0X

Wet Location Floods

	Product Description	Product Number	Lumens	Voltage	CI Code
	Predator small LED, P4 performance package, 5000K, wide flood (6x6), tenon slipfitter - knuckle (cord/leads exit bottom of slipfitter), 20kV/10kA w/indictor light extreme surge (fail off), gray super durable paint, 4FT, 12 gauge, 3 conductor cord, no PER receptacle, wet location, field adjustable lumen output	PSLED P4 50K MVOLT 66 KM 20KV GYSDP 0423 NPR WL AO	17000	120-277V	*27925E
		PSLED P4 50K XVOLT 66 KM 20KV GYSDP 0423 NPR WL AO	17000	277-480V	*27925G
	8657 GR tenon adapter	8657 GR	N/A	N/A	*116E0X
	Predator medium LED, P1 performance package, 5000K, wide flood (6x6), tenon slipfitter - knuckle (cord/leads exit bottom of slipfitter), 10kV/5kA MOV pack (fail on), gray super durable paint, 4FT, 12 gauge, 3 conductor cord, no PER receptacle, wet location, field adjustable lumens output	PMLED P1 50K MVOLT 66 KM 10KVMP GYSDP 0423 NPR WL AO	38000	120-277V	*27925J
		PMLED P1 50K XVOLT 66 KM 10KVMP GYSDP 0423 NPR WL AO	38000	277-480V	*27925L

Linear Class I Div II Fixtures- Hazardous Location

	Product Description	Product Number	Lumens	Voltage	CI Code
	Hazardous linear LED, flat glass clear lens, wide, 0-10V dimming, gray, super durable corrosion resistant paint	EMXH L24 5000LM FGCL WD MVOLT GZ10 50K 80CRI DGXD CR	5000	120-277V	*276CRU
		EMXH L24 5000LM FGCL WD 480 GZ10 50K 80CRI DGXD CR	5000	480V	*2793T6
		EMXH L48 10000LM FGCL WD MVOLT GZ10 50K 80CRI DGXD CR	10000	120-277V	*272GKR
		EMXH L48 10000LM FGCL WD 480 GZ10 50K 80CRI DGXD CR	10000	480V	*2793NJ

General Purpose High Bays

	Product Description	Product Number	Lumens	Voltage	CI Code
	Phuzion LED round high bay, standard efficiency, medium glass refractor and glass reflector, 3/4" pendant mount, field adjustable output module, gray, super durable paint	PHG 30000LM SEF MGG MVOLT 50K 70CRI PM AO DGXD	30000	120-277V	*27925M
		PHG 30000LM SEF MGG XVOLT 50K 70CRI PM AO DGXD	30000	277-480V	*27925N

Roadway/Parking/Area Lighting

	Product Description	Product Number	Lumens	Voltage	CI Code
	Autobahn cobra head, performance package, MVOLT, roadway type II, 7-pin photocontrol receptacle, field adjustable lumen output, shorting cap	ATB0 P452 MVOLT R2 5K P7 AO SH	19000	120-277V	*27925P
		ATB0 P452 XVOLT R2 5K P7 AO SH	19000	277-480V	*27925S
	Autobahn cobra head, performance package, MVOLT, roadway type II, 7-pin photocontrol receptacle, field adjustable lumen output, shorting cap	ATB2 P602 MVOLT R2 5K P7 AO SH	30000	120-277V	*27925T
		ATB2 P602 XVOLT R2 5K P7 AO SH	30000	277-480V	*27925U

Phuzion Heavy Duty High Bays

	Product Description	Product Number	Lumens	Voltage	CI Code
	Phuzion round LED high bay, 5000K, 70CRI, 3/4" pendant mount, field adjustable lumen output module, 3/4" male safety hook (PF-121-A), damp location, gray, super durable paint	PHZ 30000LM MD XVOLT 50K 70CRI PM AO HKMD DL DGXD	30000	277-480V	*27925V
	Phuzion large round LED high bay, 5000K, 70CRI, 3/4" pendant mount, field adjustable lumen output module, 3/4" male safety hook (PF-121-A), damp location, 72IN (6FT) galvanized safety chain (ships with fixture), gray, super durable paint	PHZL 60000LM ND XVOLT 50K 70CRI PM AO HKMD DL SCK72 DGXD	60000	277-480V	*27925X

Petrolux Wet Location Low Bays

	Product Description	Product Number	Lumens	Voltage	CI Code
	Petrolux LED, 5000LM nominal, medium glass lens with minimal uplight, universal mount, gray, super durable paint	PXLW 5000LM MD0 MVOLT 50K 70CRI UNM DGXD	5000	120-277V	*253SN3
		PXLW 5000LM MD0 480 50K 70CRI UNM DGXD	5000	480V	*2611EV

